


DS-2CE56C2N-IT3

720 TVL PICADIS EXIR Dome Camera




EXIR



Key features

- 1/3" PICADIS
- 1.3MP Sensor: 1280 (H) x 960 (V) Effective Pixels
- True Day/Night
- 720 TVL Horizontal Resolution
- 40m IR Distance
- Smart IR
- IP66 Weatherproof
- Wide Operating Temperature Range

Dimensions



Accessories



DS-1258ZJ
(Wall Mount)



DS-1239ZJ-1
Wall mount with
junction box for EXIR
turret cameras

DS-2CE56C2N-IT3	
Camera	
Image Sensor	1/3" PICADIS
Signal System	NTSC
Effective Pixels	1280 (H) × 960 (V)
Min. Illumination	0.1 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	NTSC: 1/30 s to 1/30,000 s
Lens	3.6mm (2.8mm,6mm,8mm,12mm,16mm optional) Angle of view: 71.4° (3.6 mm)
Lens Mount	M12
Angle Adjustment	Pan: 0 - 360° , Tilt: 0 - 75° , Rotation: 0 - 360°
Day & Night	IR cut filter with auto switch
Horizontal Resolution	720 TVL
Synchronization	Internal synchronization
Video Output	1Vp-p composite output (75 Ω/BNC)
S/N Ratio	More than 62 dB
BLC	On
General	
Working Temperature/ Humidity	-40 ° C - 60 ° C (-40 ° F - 140 ° F) Humidity 90% or less (non-condensing)
Power Supply	12 V DC
Power Consumption	Max. 5 W
Ingress Protection	IP66
IR Range	40 meters
Dimensions	Φ 114.6 × 89.1mm(Φ 4.5" × 3.5")
Weight	300 g (0.66 lbs)

Available models

DS-2CE56C2N-IT3